

Oceanus Pro ROV System

Designed,
engineered &
manufactured
on-site. | MN

A mission-ready ROV system with a diverse range of attachment options for deep-dive recovery, defense, scientific research, and complex inspection tasks.

Widely used as an inspection-class ROV system performing demanding vessel and structural inspections, the Oceanus Pro operates to a maximum standard depth of 305 m (1000 ft.) with an optional upgrade to maximum depth of 400 m (1312 ft.)[†], and a top speed of 6 knots*. A wide range of attachments, including sonar systems makes the Oceanus Pro ideal for sectors requiring ROVs to conduct diver support, border protection, port security, evidence location, search and rescue, and recovery duties.



The MarineNav Oceanus Pro offers these standard features;

- Fully vectorized thruster design delivering superior ROV maneuverability (Lateral ROV movement axis standard)
- Depth rating of 305 m (1000 ft), optional upgrade to 400 m (1312 ft)[†]
- Power over tether design
- Up to 6 knot top speed (with performance float block)^{*}
- Touch-sensitive user interface provides control of all important ROV functions
- MarineNav's Oceanus Multi-Port communication system allows rapid integration of third-party accessories, software and external processors
- 500GB solid state drive topside
- Wireless broadcasting feature allows operator screen sharing to multiple parties
- Optional MarineNav Fleet Management Suite reports status and health of ROV remotely for full tracking of individual or multiple units
- Limited 2-year warranty and MarineNav's Peace of Mind Guarantee*



**OCEANUS
PRO**

Oceanus Pro ROV system includes Pro ROV,
15-inch topside control case and Oceanus Joystick

MARINENAV
BUILT NORTH ATLANTIC TOUGH.
TRUSTED EVERYWHERE.



© 2021 MarineNav Ltd.

14-66 Panmure Island Rd – Rte 347
Panmure Island PE COA 1R0
902 838-7011
www.marinenav.ca

Oceanus Pro ROV System


Designed,
engineered &
manufactured
on-site. | MN

Specifications	
Certifications	ISO 9001: 2015
Operating Environment	Fresh or salt water, 0-50°C (32-122° F)
ROV movement and control	Full depth, horizontal and lateral movement: Auto depth, Heading hold and ROV stabilize modes
Depth Rating*	305 m (1000 ft), Optional upgrade to 400 m, (1312 ft)
Maximum Speed*	6 kn
Topside Unit Weight	18.05 kg (39.8 lbs)
ROV Weight*	17.91 kg (39.5 lbs)
Approximate Total Shipping Weight†	46.26 kg (102 lbs)
ROV Dimensions	605 mm (23.82") long, 418 mm (16.46") wide, 279 mm (10.98") height
Topside Unit Housing Material	Ultra high density polyethylene, neoprene o-ring and ABS latches
ROV Housing Material	Marine grade aluminum. Optional upgrade of anodized marine grade aluminum, protective coating available
Lights	4 x 1500 Lumen front
Camera	Internal Front: 1080p with tilt control
Camera Tilt Angle	+/- 180° Pitch (vertical rotation)
Camera Focus Range	From the face of the housing dome to infinity with manual control
Camera Field of View	120° field of view
Primary LCD Display	15" TFT active matrix panel, 1600 nits brightness (full daylight readable), 1024x786 resolution. Optional 2000 nits available
Secondary LCD Display	10.1" TFT Touch active matrix panel, 1000 nits brightness (full daylight readable), 1280 x 800 resolution
Video Output	HDMI video output
Data Storage	500 GB solid state drive topside, 64 GB solid state ROV
Topside Unit Software OS	Linux OS (MarineNav Proprietary software interface)
IMU (Sensors)	Always on, Integrated with accelerometer & magnetometer measuring telemetry including tilt, roll, pitch, and heading, auto heading, auto depth functionality
Depth Gauge	Calibrated in meters or feet (user selectable)
Topside Power	Input: 100/240 V AC 50/60 Hz, System fully operational in 60 seconds
ROV Power	Power over tether
ROV Control	MarineNav Hand Controller (IP 65)
Topside Control Case	Rugged waterproof case, transport requires one person. IP 65 when closed, IP 62 when open

Specifications - continued	
Auxiliary Ports	1 auxiliary port: capable of 1 x RS485 + Manip / 15VDC
On-Screen Display (OSD)	Real-time data including recording time, voltage, water temperature, depth, date/time stamp, heading and attitude is overlaid or embedded with video, Operator input lines available. GPS co-ordinates displayed as overlay option when paired with accessory, enabled data entry field with customized logo available
Settings	Internally saved, persist through power cycles
Wireless	Wi-Fi video broadcast to multiple devices simultaneously via integrated antenna, Wireless specification 802.11 ac/b/g/n on 2.4/5 GHZ
Tether System	Rapid deployable, neutrally buoyant tether with water-tight cable connections, optional tether deployment system available
Tether Length	500 m (1640.4 ft) maximum tether length
Available Accessory Attachments + ▲	Single axis manipulator arm, USBL, Hull crawler, Metal thickness gauge, RS485 based sonars and accessories.

- * The Oceanus Pro Plus ROV system is rated to a maximum depth rating of 300 m (1000 ft) as a standard feature. A maximum depth rating of 400 m (1312 ft) is available as an optional upgrade feature. Contact a MarineNav representative for more details.
 - * Limited Two year warranty is available to MarineNav Oceanus ROV registered within the first year of purchase. For warranty to be valid all scheduled maintenance must be adhered to according to manufacturers guidelines. Warranty excludes tampering, misuse and regular wear. Contact MarineNav for full details and restrictions of Peace of Mind Guarantee.
 - * Maximum speed test conducted with absence of all ballast weights.
 - † Approximate weight with standard primary 15" TFT active matrix panel.
 - Estimated dry weight
 - ‡ Choice of available options will change overall shipping weight. Shipping weight based on 100 m tether, ROV unit, topside & hand controller.
 - ▲ Some accessories require use of the MarineNav multi port communication system.
 - ▲ Oceanus ROVs may exceed recommended depth ratings of available accessories. Consult manufacturer specifications for all accessories prior to use. MarineNav Ltd. is an ISO 9001:2015 certified company. Our certified Quality Management System ensures that each unit we produce adheres to the strictest standards and complies with customer requirements.
- While we strive to ensure the accuracy of all items and descriptions in this document, this is not always possible. Specifications, options, and availability are subject to change without notice. Errors and omissions excepted. We reserve the right to limit quantities.

Powerful vectorized thruster design



ROV powered over tether

1080p high definition camera

4 x 1500 lumen lights

Top speed up to 6 knots



ROV weight 17.91 kg

Depth rating of 305m*

MARINE NAV
BUILT NORTH ATLANTIC TOUGH.
TRUSTED EVERYWHERE.



© 2020 MarineNav Ltd.

1466 Panmure Island Rd – Rte 347
Panmure Island PE COA 1R0
902 838-7011
www.marinenav.ca